



• Brine tank, water softener and rack not included

chemical free **cleaning** and **disinfecting**

- Compact modular design
- High production capacity
- High-level disinfection
- Completely safe
- Removes and prevents biofilm
- Highly cost effective in terms of:
 - Low energy consumption
 - Parts / Service / Maintenance
- Easy to Install & operate
- Easy to maintain
- Eradicates all pathogens
- Remote diagnostics
- Standard components

SPECIFICATIONS

MODEL: EAW 1

Power requirements	Volts	240
	Amps	30
	Cycles	50/60
	Gallon/minute	0.5
	Liter/minute	1.89
	Bar	1.5
	PSI	21.75
Height	Imperial (in.)	48
	Metrix (mm)	1219
Width	Imperial (in.)	15 ¾
	Metrix (mm)	400
Depth	Imperial (in.)	7 ⅞
	Metrix (mm)	200
Weight	Imperial (lbs.)	71.7
	Metrix (kg.)	32.5
Max. Production volume HOCl	Gallon/hour	19
	Liter/hour	72
Max. Concentration HOCl	mg/l (ppm)	475 >
	ORP	900 >
	pH	6.5-7.5
Max. Production volume NaOH	Gallon/hour	2
	Liter/hour	8
Max. Concentration NaOH	mg/l (ppm)	200 >
	ORP	< 800
	pH	11-12.5
Brine tank		-
Water softener		-
Remote monitoring		✓
Self-Installation		✓