

chemical free cleaning and **disinfecting**



- Compact modular design
- High production capacity
- Flexible up-scaling
- Completely safe
- Removes and prevents biofilm
- Highly cost effective in terms of:
Low energy consumption
Parts / Service
Maintenance
- Easy to Install & operate
- Easy to maintain
- High-level disinfection
- Eradicates all pathogens
- Remote diagnostics
- Standard components

SPECIFICATIONS MODEL: EAW-1

Power requirements	Volts	240
	Amps	30
	Cycles	50/60
Water supply	Liters/minute	1.85
(minimums required for softener)	Gal/minute	0.5
Min. water pressure	Bar	2.5
	PSI	36
Height	Metric	1740mm
	Imperial	68.5 in
Width	Metric	640mm
	Imperial	25
Depth	Metric	680mm
	Imperial	27 in.
Weight	Metric	130 kg
	Imperial	440.9 lbs.
Max. Production volume HOCL	Liters/hour	90
	Gallons/hour	24
Max. Concentration HOCl	mg/l (ppm)	550 >
ORP		800 >
pH		6.8
Max. Production volume NaOH	Liters/hour	22
	Gallons/hour	6
Max. Concentration NaOH	mg/l (ppm)	200 >
ORP		< 800
pH		11
Adjustable height float switch w/stock tank		3
Water softener – salt tank		1